

14oraitaliana

Spirito Eclettico
Eclectic Spirit



Slice



**La decisa matericità che caratterizza Slice trova ispirazione
e punto d'incontro tra legno e creta.
Accumuli di terra premuta mista a legname diversamente rifinito
riecheggiano in una superficie composta da
listelli 10x60 e 10x20 cm disponibili in cinque varianti colore:
ICE, DUST, MUD, MOU, PITCH.
Le colorazioni neutre che si muovono tutte su contenuti
spostamenti di tono si presentano in sette diverse texture
utilizzabili unicamente in combinazione tra loro.
Corposità e colore sono i tratti salienti di Slice, una collezione che
si presta ad arredare ambienti con incisiva sobrietà.**

Slice's distinct materiality is characterized and inspired by the meeting of
two different substances, wood and clay.
Accumulations of pressed wood mixed with differently finished timber re-
sound in a surface composed in 10x60 / 3,93"x24" and 10x20 / 3,93"x8"
slats available in five color variants: ICE, DUST, MUD, MOU, PITCH
The neutral colorations that move though contained displacement of
tone appear in seven different textures, which can me combined among
themselves in a unique manner. Full bodiedness and color are the salient
traits of Slice, a collection that lends itself to furnishing environments with
strong sobriety.

Slice

Ice
10x60 - 3,93"x24"

Slice

GRES PORCELLANATO - NATURALE RETTIFICATO
PORCELAIN STONEWARE - NATURAL RECTIFIED

spessore 10 mm
thickness 0,4"



10x60 - 3,54"x24"



10x20 - 3,54"x8"



ICE
10x60
0142511
10x20
0139880



DUST
10x60
0142512
10x20
0139870



MUD
10x60
0142513
10x20
0139878












MOU
10x60
0142514
10x20
0142781



PITCH
10x60
0142515
10x20
0139877

Dati Tecnici / Technical Info

NORMA STANDARD	CARATTERISTICHE FEATURES	VALORE PRESCRITTO VALUE REQUIRED	
	DIMENSIONI lunghezza e larghezza spessore rettilinearità degli spigoli ortogonalità planarità	SIZES length and width thickness straighthness of edges wedging fiatness	± 0,6% ± 5% ± 0,5% ± 0,6% ± 0,5%
	ISO 10545.2		Conforme In conformity with standard
	ISO 10545.3	Assorbimento d'acqua Water absorption	≤ 0,5%
	ASTM C373		≤ 0,5%
	ISO 10545.4	Resistenza alla flessione Bending strength	> 35 N/mm2
	ASTM C658		Resiste Resistant
	ISO 10545.9	Resistenza agli sbalzi termici Thermal shocks resistant	Resistente Resistant
	ASTM C484		no samples must show visible defects Resiste Resistant
	ISO 10545.12	Resistenza al gelo Frost resistance	Resistente Resistant
	ASTM C1026		Unaffected Unaffected
	ISO 10545.13	Resistenza agli attacchi chimici Resistance to chemicals attacks	GA GLA GHA
	ASTM C650		Resiste Resistant Unaffected
	ISO 10545.7	Resistenza all'abrasione Resistance to abrasion	-
	ASTM C648		Classe PEI 4
	DIN 51130	Resistenza allo scivolamento Skid resistance	R9
	DCoF (Bot 3.000) ANSI A 137.1:2012		≥ 0,42 wet >0,42
	ISO 10545.14	Resistenza alle macchie Resistance to stains	Valore minimo Min. value 3
			5

14oraitaliana
TARGET GROUP

VIA DEL CROCIALE, 69
41042 FIORANO MODENESE_MO
ITALY

Phone +39 0536 405150
14oraitaliana.com